



Systematic Modelling and Crystal Size Distribution Control for Batch Crystallization Processes

Abdul Samad, Noor Asma Fazli; Singh, Ravendra; Sin, Gürkan; Gernaey, Krist; Gani, Rafiqul

Publication date:
2011

[Link back to DTU Orbit](#)

Citation (APA):

Abdul Samad, N. A. F., Singh, R., Sin, G., Gernaey, K., & Gani, R. (2011). *Systematic Modelling and Crystal Size Distribution Control for Batch Crystallization Processes*. Abstract from 2nd European Conference on Process Analytics and Control Technology, Glasgow, Scotland.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Systematic Modeling and Crystal Size Distribution Control for Batch Cooling Crystallization Processes

Noor Asma Fazli Abdul Samad¹, Ravendra Singh¹, Gürkan Sin¹, Krist V. Gernaey² and Rafiqul Gani^{*1}

(1) Computer Aided Process-Product Engineering Center (CAPEC), Department of Chemical and Biochemical Engineering, Søtofts Plads, Building 229, Technical University of Denmark, DK-2800 Lyngby, Denmark

(2) Center for Process Engineering and Technology (PROCESS), Department of Chemical and Biochemical Engineering, Søtofts Plads, Building 229, Technical University of Denmark, DK-2800 Lyngby, Denmark

Crystallization processes form an important class of separation methods that are frequently used in the chemical, the pharmaceutical and the food industry. The specifications of the crystal product are usually given in terms of crystal size, shape and purity. In order to predict the desired crystal morphology by means of model-based approaches, appropriate models covering the effects of the various operational parameters on the behavior of the crystals are necessary. Usually the main difficulty in batch crystallization is to accomplish a uniform CSD. There are many ways to enhance the control of CSD such as to use supersaturation control which drives the process within the metastable zone or by determining the amount and size of seeds that should be added into a crystallizer through seed recipe design approach. Therefore, there is a need for a generic crystallization model that can provide a better understanding of crystallization operations and from which a large number of specific models for different crystallization processes can be generated. Furthermore, to control and monitor the crystallization operations and to ensure that the desired CSD is achieved, an appropriate Process Analytical Technology (PAT) system needs to be available. That is, the design of process control and product monitoring system that will obtain the desired end-product properties is also needed.

The generic multi-dimensional model-based framework of batch cooling crystallization processes has been developed covering a wide range of crystallization models and operational scenarios. The use of the generic model will be illustrated, in this paper, through the ICAS-PAT software for design of process monitoring and control system. ICAS-PAT consists of a model library and a knowledge base that allows the user to design/validate PAT systems through a systematic computer aided framework. The generic crystallizer model has been implemented in the ICAS-PAT model library. The application of the model-based framework will be highlighted through a batch cooling crystallization processes where the objective is to obtain a desired CSD. In order to predict the desired CSD at the end of the batch, an analytical CSD estimator based on the assumption of the constant supersaturation will be employed. Through this estimator, supersaturation set-point can be identified indicating that by maintaining the supersaturation at its set-point will result into achieving the specified CSD consistently. Thus using the ICAS-PAT, the crystallization operations can be monitored and controlled according to the required set-point during the batch run. For this purpose, the generation of the needed crystallization model will be illustrated together with its use in the ICAS-PAT software.

Keywords: multidimensional, crystal size distribution, crystal shape

* Corresponding author (Email: rag@kt.dtu.dk, Tel. +45 45252882, Fax: +45 45932906)